

Communications - AC 700F Communication interfaces

Freelance hardware selector

The AC 700F controller PM 783F includes a Profibus DP Master communications module that makes it possible to access a wide range of field devices and third-party systems.



Specific feature ¹	CI 773F
General info	
Article number	3BDH000395R0001
Communication protocol	Communication Interface, PROFIBUS DP Master
Life cycle status	Active
Transmission speed	9.6 kBit/s to 12 MBit/s
Line redundancy	No
Hot Swap	Yes
Dimensions	
Width	28 mm
Height	135 mm
Depth	75 mm
Weight	96 g
Environment and certification	
RoHS compliance	Directive 2011/65/EU, (EU) 2015/863
WEEE compliance	Directive 2012/19/EU

¹ For detailed information on each module, please visit: freelancehardwareselector.automation.abb.com

solutions.abb/freelance
solutions.abb/controlsystems

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2024 ABB All rights reserved